

MATERIAL SAFETY DATA SHEET PAGE #1
FOR COATINGS, RESINS AND RELATED MATERIALS
DATE OF PREPARATION - 04/29/2010

MANUFACTURER'S NAME : Kelley Technical Coatings
ADDRESS : 1445 South 15th Street
ADDRESS : PO Box 3726
ADDRESS :
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 418-5086-

SECTION I -- PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION :153
PRODUCT CLASS : Latex Paint
TRADE NAME : PATIO PERFECT, STONE CREEK
HMIS INFORMATION : HEALTH : 02
FLAMMABILITY : 01
REACTIVITY : 01
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

SECTION II -- HAZARDOUS INGREDIENTS

---- INGREDIENT ----	%BY	ACGIH	OSHA	SAR NUIS
MATERIAL DESCRIPTION	Cas	WEIGHT	T.L.V.	P.E.L 313 PGMT
Butoxy Dipropanol				
29911-28-2	1.9846	Not Estab.	Not Estab.	Y N
Ethylene Glycol				
107-21-1	2.3253		N N	

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

SECTION III -- PHYSICAL DATA

LOWER EXPLOSION LEVEL 1.0 - 1.2

BOILING RANGE HIGH 493 DF LOW 388 DF
VAPOR PRESSURE 1.00 MMHG @ 68DF
VAPOR DENSITY HEAVIER THAN AIR
EVAPORATION RATE N/A
WEIGHT PER GALLON 12.97
% VOLATILE BY VOLUME 56.12

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 153 DATE OF PREPARATION - 04/29/10
TRADE NAME PATIO PERFECT, STONE CREEK,

% VOLATILE BY WEIGHT 35.93
VOC --- LBS/GAL 0.58 LBS/GAL No Water 1.14
GRAMS/LITER 69.36 GRAMS/LITER 137

SECTION IV -- FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION OSHA - CLASS III-B
DOT - NOT REGULATED
LOWEST FLASH POINT T.C.C. 201 DF
LOWER EXPLOSION LEVEL (LEL) 0.6%
Extinguishing Media: (No) - Foam (No) - Alcohol Foam (No) - CO2
(No) - Dry Chemical (No) - Water Fog (No) - Other
Unusual Fire and Explosion Hazards: - None
Special Fire Fighting Procedures: - None

SECTION V -- HEALTH HAZARD DATA

To the best of our knowledge, this product does not
contain any carcinogenic ingredients.
Effects of Overexposure: - None
Primary Route(s) of Entry: (No) - Dermal (No) - Inhalation
(No) - Ingestion
Emergency and First Aid Procedures: - None
Medical Conditions Prone to Aggravation by Exposure:
- Pre-existing respiratory, eye and skin conditions.

SECTION VI -- REACTIVITY DATA

Stability: () - Unstable (X) - Stable

Hazardous Polymerization: () - May Occur (X) - Will Not Occur

Hazardous Decomposition Products: - None

Conditions to Avoid: - None

Incompatibility (Materials to Avoid): - None

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 153

DATE OF PREPARATION - 04/29/10

TRADE NAME PATIO PERFECT, STONE CREEK,

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Leaked or Spilled: - Shut off and eliminate leaks. Contain spill to prevent run-off to sewers, streams, and other bodies of water. Small spills can be cleaned up with sand or other absorbent material. Large spills must be reported to local agencies.

Waste Disposal Method: - Dispose of this product in accordance with all applicable local, county, state, and federal regulations.

SECTION VIII -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: - If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator. Consult the respirator manufactures literature to ensure that the respirator will provide adequate protection.

Ventilation: - Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

Protective Gloves: - Appropriate chemical resistant gloves should be worn.

Eye Protection: - Wear safety glasses or goggles to protect against exposure.

Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: - Keep from freezing.