



-----  
LOWER EXPLOSION LEVEL 1.0 - 1.2  
BOILING RANGE HIGH 493 DF LOW 244 DF  
VAPOR PRESSURE 1.00 MMHG @ 68DF  
VAPOR DENSITY HEAVIER THAN AIR  
EVAPORATION RATE SLOWER THAN BUTYL ACETATE

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 430 DATE OF PREPARATION - 04/27/11  
TRADE NAME SMART SEAL AQUA SEAL, WHITE,

WEIGHT PER GALLON 11.98  
% VOLATILE BY VOLUME 58.6  
% VOLATILE BY WEIGHT 41.02  
VOC --- LBS/GAL 0.52 LBS/GAL No Water 1.1  
GRAMS/LITER 62.96 GRAMS/LITER 131.99

-----  
SECTION IV -- FIRE AND EXPLOSION DATA  
-----

FLAMMABILITY CLASSIFICATION OSHA - CLASS III-B  
DOT - NOT REGULATED  
LOWEST FLASH POINT T.C.C. 201 DF  
LOWER EXPLOSION LEVEL (LEL) 0.6%  
Extinguishing Media: (No) - Foam (No) - Alcohol Foam (No) - CO2  
(No) - Dry Chemical (No) - Water Fog (No) - Other  
Unusual Fire and Explosion Hazards: - None  
Special Fire Fighting Procedures: - None

-----  
SECTION V -- HEALTH HAZARD DATA  
-----

To the best of our knowledge, this product does not  
contain any carcinogenic ingredients.  
Effects of Overexposure: - None  
Primary Route(s) of Entry: (No) - Dermal (No) - Inhalation  
(No) - Ingestion  
Emergency and First Aid Procedures: - None  
Medical Conditions Prone to Aggravation by Exposure:  
- Pre-existing respiratory, eye and skin conditions.

-----  
SECTION VI -- REACTIVITY DATA

-----  
Stability: ( ) - Unstable (X) - Stable  
Hazardous Polymerization: ( ) - May Occur (X) - Will Not Occur  
Hazardous Decomposition Products: - None  
Conditions to Avoid: - None  
Incompatibility (Materials to Avoid): - None

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 430 DATE OF PREPARATION - 04/27/11  
TRADE NAME SMART SEAL AQUA SEAL, WHITE,

-----  
SECTION VII -- SPILL OR LEAK PROCEDURES  
-----

Steps to be Taken in Case Material is Leaked or Spilled: - Shut off and eliminate leaks. Contain spill to prevent run-off to sewers, streams, and other bodies of water. Small spills can be cleaned up with sand or other absorbent material. Large spills must be reported to local agencies.  
Waste Disposal Method: - Dispose of this product in accordance with all applicable local, county, state, and federal regulations.

-----  
SECTION VIII -- SAFE HANDLING AND USE INFORMATION  
-----

Respiratory Protection: - If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator. Consult the respirator manufactures literature to ensure that the respirator will provide adequate protection.  
Ventilation: - Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.  
Protective Gloves: - Appropriate chemical resistant gloves should be worn.  
Eye Protection: - Wear safety glasses or goggles to protect against exposure.  
Hygienic Practices: - Remove paint from skin contact after exposure.

-----  
SECTION IX -- SPECIAL PRECAUTIONS  
-----

Precautions to be Taken in Handling and Storing: - Keep from freezing.