
LOWER EXPLOSION LEVEL 1.0 - 1.2
BOILING RANGE HIGH 493 DF LOW 244 DF
VAPOR PRESSURE 1.00 MMHG @ 68DF
VAPOR DENSITY HEAVIER THAN AIR
EVAPORATION RATE SLOWER THAN BUTYL ACETATE

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 432 DATE OF PREPARATION - 04/27/11
TRADE NAME SMART SEAL AQUA SEAL,, BLUE HEAVEN

WEIGHT PER GALLON 11.33
% VOLATILE BY VOLUME 59.16
% VOLATILE BY WEIGHT 43.78
VOC --- LBS/GAL 0.53 LBS/GAL No Water 1.12
GRAMS/LITER 63.39 GRAMS/LITER 134.38

SECTION IV -- FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION OSHA - CLASS III-B
DOT - NOT REGULATED
LOWEST FLASH POINT T.C.C. 201 DF
LOWER EXPLOSION LEVEL (LEL) 0.6%
Extinguishing Media: (No) - Foam (No) - Alcohol Foam (No) - CO2
(No) - Dry Chemical (No) - Water Fog (No) - Other
Unusual Fire and Explosion Hazards: - None
Special Fire Fighting Procedures: - None

SECTION V -- HEALTH HAZARD DATA

To the best of our knowledge, this product does not
contain any carcinogenic ingredients.
Effects of Overexposure: - None
Primary Route(s) of Entry: (No) - Dermal (No) - Inhalation
(No) - Ingestion
Emergency and First Aid Procedures: - None
Medical Conditions Prone to Aggravation by Exposure:
- Pre-existing respiratory, eye and skin conditions.

SECTION VI -- REACTIVITY DATA

Stability: () - Unstable (X) - Stable
Hazardous Polymerization: () - May Occur (X) - Will Not Occur
Hazardous Decomposition Products: - None
Conditions to Avoid: - None
Incompatibility (Materials to Avoid): - None

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 432 DATE OF PREPARATION - 04/27/11
TRADE NAME SMART SEAL AQUA SEAL,, BLUE HEAVEN

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Leaked or Spilled: - Shut off and eliminate leaks. Contain spill to prevent run-off to sewers, streams, and other bodies of water. Small spills can be cleaned up with sand or other absorbent material. Large spills must be reported to local agencies.
Waste Disposal Method: - Dispose of this product in accordance with all applicable local, county, state, and federal regulations.

SECTION VIII -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: - If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator. Consult the respirator manufactures literature to ensure that the respirator will provide adequate protection.
Ventilation: - Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.
Protective Gloves: - Appropriate chemical resistant gloves should be worn.
Eye Protection: - Wear safety glasses or goggles to protect against exposure.
Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: - Keep from freezing.