

MATERIAL SAFETY DATA SHEET PAGE #1
FOR COATINGS, RESINS AND RELATED MATERIALS

DATE OF PREPARATION – 1/1/10

MANUFACTURER'S NAME : Kelley Technical Coatings

ADDRESS : 1445 South 15th Street
ADDRESS : PO Box 3726
ADDRESS :
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 418-5086-

SECTION I -- PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION :5200B
PRODUCT CLASS : Epoxy
TRADE NAME : Smart Seal, WB Epoxy Floor Coating, Tan, Base
HMIS INFORMATION : HEALTH : 02
FLAMMABILITY : 01
REACTIVITY : 01
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

SECTION II -- HAZARDOUS INGREDIENTS

---- INGREDIENT ----	%BY	ACGIH	OSHA	SAR NUIS
MATERIAL DESCRIPTION	Cas	WEIGHT	T.L.V.	P.E.L 313 PGMT
2-BUTOXYETHANOL				
111-76-2	2.0741	25PPM	50PPM	Y N
Glycol Ether EP				
2807-30-9	7.5637		Y Y	

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

SECTION III -- PHYSICAL DATA

LOWER EXPLOSION LEVEL 1.0 - 1.2
BOILING RANGE HIGH 343 DF LOW 301 DF
VAPOR PRESSURE 68.00 MMHG @ 68DF
VAPOR DENSITY HEAVIER THAN AIR
EVAPORATION RATE FASTER THAN BUTYL ACETATE
WEIGHT PER GALLON 11.47
% VOLATILE BY VOLUME 51.63
% VOLATILE BY WEIGHT 36.94
VOC --- LBS/GAL 0.65 LBS/GAL No Water 1.15
GRAMS/LITER 77.97 GRAMS/LITER 137.94

SECTION IV -- FIRE AND EXPLOSION DATA

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 5200B

DATE OF PREPARATION – 1/1/10

TRADE NAME Smart Seal, WB Epoxy Floor, Coating, Tan, Base

FLAMMABILITY CLASSIFICATION OSHA - CLASS III-B

DOT - NOT REGULATED

LOWEST FLASH POINT T.C.C. 201 DF

LOWER EXPLOSION LEVEL (LEL) 1.1%

Extinguishing Media: (No) - Foam (No) - Alcohol Foam (No) - CO2

(No) - Dry Chemical (No) - Water Fog (No) - Other

Unusual Fire and Explosion Hazards: - None

Special Fire Fighting Procedures: - None

SECTION V -- HEALTH HAZARD DATA

To the best of our knowledge, this product does not

contain any carcinogenic ingredients.

Effects of Overexposure: - None

Primary Route(s) of Entry: (No) - Dermal (No) - Inhalation

(No) - Ingestion

Emergency and First Aid Procedures: - None

Medical Conditions Prone to Aggravation by Exposure:

- Pre-existing respiratory, eye and skin conditions.

SECTION VI -- REACTIVITY DATA

Stability: () - Unstable (X) - Stable

Hazardous Polymerization: () - May Occur (X) - Will Not Occur

Hazardous Decomposition Products: - None

Conditions to Avoid: - None

Incompatibility (Materials to Avoid): - None

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Leaked or Spilled: - Shut off and eliminate leaks. Contain spill to prevent run-off to sewers, streams, and other bodies of water. Small spills can be cleaned up with sand or other absorbent material. Large spills must be reported to local agencies.

Waste Disposal Method: - Dispose of this product in accordance with all applicable local, county, state, and federal regulations.

SECTION VIII -- SAFE HANDLING AND USE INFORMATION

MANUFACTURER'S CODE 5200B

DATE OF PREPARATION – 1/1/10

TRADE NAME Smart Seal, WB Epoxy Floor, Coating, Tan, Base

Respiratory Protection: - None

Ventilation: - None

Protective Gloves: - None

Eye Protection: - None

Other Protective Equipment: - None

Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: - Keep from freezing.

Other Precautions: - None