

MATERIAL SAFETY DATA SHEET PAGE #1  
FOR COATINGS, RESINS AND RELATED MATERIALS  
DATE OF PREPARATION – 1/1/10

MANUFACTURER'S NAME : Kelley Technical Coatings  
ADDRESS : 1445 South 15th Street  
ADDRESS : PO Box 3726  
ADDRESS :  
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-  
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 418-5086-

-----  
SECTION I -- PRODUCT IDENTIFICATION  
-----

MANUFACTURER'S CODE IDENTIFICATION :5200C  
PRODUCT CLASS : Catalyst  
TRADE NAME : WATERBASE EPOXY, FLOOR PAINT CATALYST  
HMIS INFORMATION : HEALTH : 03  
FLAMMABILITY : 01  
REACTIVITY : 02  
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

-----  
SECTION II -- HAZARDOUS INGREDIENTS  
-----

| ---- INGREDIENT ---- | %BY    | ACGIH  | OSHA   | SAR NUIS       |
|----------------------|--------|--------|--------|----------------|
| MATERIAL DESCRIPTION | Cas    | WEIGHT | T.L.V. | P.E.L 313 PGMT |
| GLYCOL ETHER EP      |        |        |        |                |
| 2807-30-9            | 21.709 |        | Y N    |                |
| ACETIC ACID          |        |        |        |                |
| 64-19-7              | 1.6313 |        | N N    |                |

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

-----  
SECTION III -- PHYSICAL DATA  
-----

LOWER EXPLOSION LEVEL 1.0 - 1.2  
BOILING RANGE HIGH 301 DF LOW 301 DF

VAPOR PRESSURE 68.00 MMHG @ 68DF  
VAPOR DENSITY HEAVIER THAN AIR  
EVAPORATION RATE FASTER THAN BUTYL ACETATE  
WEIGHT PER GALLON 8.66  
% VOLATILE BY VOLUME 69.79  
% VOLATILE BY WEIGHT 65.47  
VOC --- LBS/GAL 2.01 LBS/GAL No Water 3.56  
GRAMS/LITER 241.33 GRAMS/LITER 427.7

---

SECTION IV -- FIRE AND EXPLOSION DATA

---

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 5200C DATE OF PREPARATION – 1/1/10  
TRADE NAME WATERBASE EPOXY, FLOOR PAINT, CATALYST

FLAMMABILITY CLASSIFICATION OSHA - CLASS III-B  
DOT - NOT REGULATED  
LOWEST FLASH POINT T.C.C. 201 DF  
LOWER EXPLOSION LEVEL (LEL) N/A%  
Extinguishing Media: (No) - Foam (No) - Alchohol Foam (No) - CO2  
(No) - Dry Chemical (No) - Water Fog (No) - Other  
Unusual Fire and Explosion Hazards: - None  
Special Fire Fighting Procedures: - None

---

SECTION V -- HEALTH HAZARD DATA

---

To the best of our knowledge, this product does not  
contain any carcinogenic ingredients.  
Effects of Overexposure: - None  
Primary Route(s) of Entry: (No) - Dermal (No) - Inhalation  
(No) - Ingestion  
Emergency and First Aid Procedures: - None  
Medical Conditions Prone to Aggravation by Exposure:  
- Pre-existing respiratory, eye and skin conditions.

---

SECTION VI -- REACTIVITY DATA

---

Stability: ( ) - Unstable (X) - Stable  
Hazardous Polymerization: ( ) - May Occur (X) - Will Not Occur

Hazardous Decomposition Products: - None  
Conditions to Avoid: - None  
Incompatibility (Materials to Avoid): - None

---

### SECTION VII -- SPILL OR LEAK PROCEDURES

---

Steps to be Taken in Case Material is Leaked or Spilled: - Shut off and eliminate leaks. Contain spill to prevent run-off to sewers, streams, and other bodies of water. Small spills can be cleaned up with sand or other absorbent material. Large spills must be reported to local agencies.  
Waste Disposal Method: - Dispose of this product in accordance with all applicable local, county, state, and federal regulations.

---

### SECTION VIII -- SAFE HANDLING AND USE INFORMATION

---

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 5200C                      DATE OF PREPARATION – 1/1/10  
TRADE NAME              WATERBASE EPOXY, FLOOR PAINT, CATALYST

Respiratory Protection: - None  
Ventilation: - None  
Protective Gloves: - None  
Eye Protection: - None  
Other Protective Equipment: - None  
Hygienic Practices: - Remove paint from skin contact after exposure.

---

### SECTION IX -- SPECIAL PRECAUTIONS

---

Precautions to be Taken in Handling and Storing: - Keep from freezing.  
Other Precautions: - None