



-----  
LOWER EXPLOSION LEVEL 1.0 - 1.2  
BOILING RANGE HIGH 343 DF LOW 300 DF  
VAPOR PRESSURE 3.00 MMHG @ 68DF  
VAPOR DENSITY HEAVIER THAN AIR  
EVAPORATION RATE SLOWER THAN BUTYL ACETATE  
WEIGHT PER GALLON 12.94  
% VOLATILE BY VOLUME 27.71  
% VOLATILE BY WEIGHT 15.71  
VOC --- LBS/GAL 2.03 LBS/GAL No Water 2.03  
GRAMS/LITER 243.65 GRAMS/LITER 243.65

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 520B

DATE OF PREPARATION - 01-01-10

TRADE NAME Duraseal WHITE BASE,

-----  
SECTION IV -- FIRE AND EXPLOSION DATA  
-----

FLAMMABILITY CLASSIFICATION OSHA - CLASS II

DOT - COMBUSTIBLE LIQUID UN 1263

LOWEST FLASH POINT T.C.C. 110 DF

LOWER EXPLOSION LEVEL (LEL) 1%

Extinguishing Media: (Yes) - Foam (No) - Alcohol Foam (Yes) - CO2  
(Yes) - Dry Chemical (Yes) - Water Fog

Unusual Fire and Explosion Hazards: - Flammable vapors may form explosive mixtures with air.

Special Fire Fighting Procedures: - Avoid solid stream of water, use fog for cooling.

-----  
SECTION V -- HEALTH HAZARD DATA  
-----

To the best of our knowledge, this product does not contain any carcinogenic ingredients.

Effects of Overexposure: - Liquid may cause eye burns. Prolonged skin contact with liquid may cause irritation. Eye, nose and throat irritation may result from exposure to vapor. Narcotic effects occur at higher concentrations of vapor.

Primary Route(s) of Entry: (X) - Dermal (X) - Inhalation (X) - Ingestion

Emergency and First Aid Procedures:

- Eye contact: Irrigate immediately and thoroughly with water at least 15 minutes and get medical attention.
- Skin contact: Flush immediately and thoroughly with water.
- Inhalation: Remove from exposure, treat symptomatically and get medical attention.

Medical Conditions Prone to Aggravation by Exposure:

- Pre-existing Respiratory, Eye and Skin Conditions.

---

## SECTION VI -- REACTIVITY DATA

---

Stability: ( ) - Unstable (X) - Stable

Hazardous Polymerization: ( ) - May Occur (X) - Will Not Occur

Hazardous Decomposition Products: - As with any other organic material, combustion will produce carbon dioxide and probably carbon monoxide.

Conditions to Avoid: - Not applicable.

Incompatibility (Materials to Avoid): - Oxidizing materials can cause a vigorous reaction.

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 520B

DATE OF PREPARATION - 01-01-10

TRADE NAME Duraseal WHITE BASE,

---

## SECTION VII -- SPILL OR LEAK PROCEDURES

---

Steps to be Taken in Case Material is Leaked or Spilled:

- Eliminate all ignition sources. Flush spill away with water spray.
- Small spills may be collected with absorbant material.

Waste Disposal Method:

- Mix with a compatible chemical which is less combustible and incinerate.
- Observe all federal, state, and local laws concerning health and pollution.

---

## SECTION VIII -- SAFE HANDLING AND USE INFORMATION

---

Respiratory Protection: - A NIOSH approved respirator for organic vapors should be worn if needed.

Ventilation: - Local exhaust recommended.

- Mechanical (General) recommended.
- Special: None known.

Protective Gloves: - Should be worn.

Eye Protection: - Safety glasses should be worn in any type of industrial operation.

Other Protective Equipment: - Safety shower and eye bath in work area.

Hygienic Practices: - Remove paint from skin contact after exposure.

---

## SECTION IX -- SPECIAL PRECAUTIONS

---

Precautions to be Taken in Handling and Storing: -

Keep away from heat, sparks and open flame.

Keep container closed. Avoid eye contact, prolonged skin contact, and inhalation of high concentrations of vapor. Use with ventilation adequate to maintain vapor concentrations below the TLV of 50 PPM.

Other Precautions: - Hazardous product residue may remain after the product has been removed from its container. Do not reuse "empty" container without commercial cleaning or reconditioning. See also 29 code of federal regulation 1910.1000.