

MATERIAL SAFETY DATA SHEET PAGE #1
FOR COATINGS, RESINS AND RELATED MATERIALS
DATE OF PREPARATION - 01/01/10

MANUFACTURER'S NAME : Kelley Technical Coatings
ADDRESS : 1445 South 15th Street
ADDRESS : PO Box 3726
ADDRESS :
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 363-9721-

SECTION I -- PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION :770C
PRODUCT CLASS : Catalyst
TRADE NAME : SMART SEAL PRIME IT CATALYST
HMIS INFORMATION : HEALTH : 02
FLAMMABILITY : 01
REACTIVITY : 01
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

SECTION II -- HAZARDOUS INGREDIENTS

---- INGREDIENT ----	%BY	ACGIH	OSHA	SAR NUIS
MATERIAL DESCRIPTION	Cas	WEIGHT	T.L.V.	P.E.L 313 PGMT
2-BUTOXYETHANOL				
111-76-2	5.7804	25PPM	50PPM	Y N

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered
a trade secret.

SECTION III -- PHYSICAL DATA

LOWER EXPLOSION LEVEL 1.0 - 1.2
BOILING RANGE HIGH 343 DF LOW 336 DF
VAPOR PRESSURE 0.88 MMHG @ 68DF

VAPOR DENSITY HEAVIER THAN AIR
EVAPORATION RATE SLOWER THAN BUTYL ACETATE
WEIGHT PER GALLON 9.09
% VOLATILE BY VOLUME 40
% VOLATILE BY WEIGHT 36.01
VOC --- LBS/GAL 0.53 LBS/GAL No Water 0.78
GRAMS/LITER 63.08 GRAMS/LITER 94.16

SECTION IV -- FIRE AND EXPLOSION DATA

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 770C DATE OF PREPARATION - 01/01/10
TRADE NAME SMART SEAL PRIME IT CATALYST,

FLAMMABILITY CLASSIFICATION OSHA - CLASS III-B
DOT - NOT REGULATED
LOWEST FLASH POINT T.C.C. 201 DF
LOWER EXPLOSION LEVEL (LEL) 1.1%
Extinguishing Media: (No) - Foam (No) - Alcohol Foam (No) - CO2
(No) - Dry Chemical (No) - Water Fog (No) - Other
Unusual Fire and Explosion Hazards: - None
Special Fire Fighting Procedures: - None

SECTION V -- HEALTH HAZARD DATA

To the best of our knowledge, this product does not
contain any carcinogenic ingredients.
Effects of Overexposure: - None
Primary Route(s) of Entry: (No) - Dermal (No) - Inhalation
(No) - Ingestion
Emergency and First Aid Procedures: - None
Medical Conditions Prone to Aggravation by Exposure:
- Pre-existing respiratory, eye and skin conditions.

SECTION VI -- REACTIVITY DATA

Stability: () - Unstable (X) - Stable
Hazardous Polymerization: () - May Occur (X) - Will Not Occur
Hazardous Decomposition Products: - None

Conditions to Avoid: - None

Incompatibility (Materials to Avoid): - None

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Leaked or Spilled: - None

Waste Disposal Method: - None

SECTION VIII -- SAFE HANDLING AND USE INFORMATION

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 770C

DATE OF PREPARATION - 01/01/10

TRADE NAME SMART SEAL PRIME IT CATALYST,

Respiratory Protection: - None

Ventilation: - None

Protective Gloves: - None

Eye Protection: - None

Other Protective Equipment: - None

Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: - None

Other Precautions: - None