

# SAFETY DATA SHEET

**Product Name: SMART SEAL ROUGH PRIME**

**Product Code: 660 Catalyst**

**Date issued: 5/27/2015**

---

## SECTION 1 : IDENTIFICATION

Product Name SMART SEAL ROUGH PRIME

Product Code # 660 Catalyst

Identified Uses Protective Coating

Manufacturer: Kelley Technical Coatings  
1445 South 15<sup>th</sup> Street  
P.O. Box 3726  
Louisville, Kentucky 40201-3726

Emergency Contact Number: Day: 502-636-2561 Night: 800-424-9300

Information Telephone Number: 502-636-2561

---

## SECTION 2 : HAZARDS IDENTIFICATION

Flammable Liquid 3  
Aspiration Hazard 1  
Skin Corrosion 1A-1C  
Skin Sensitization 1  
Acute Toxicity - Inhalation 4  
Carcinogenicity 2  
Specific Target Organ Toxicity (Single Exposure) 3

### GHS Classification

### GHS Label Elements

#### Hazard Symbols



Signal Word Danger

#### Hazard Statements

H226 Flammable liquid and vapor  
H304 May be fatal if swallowed and enters airways  
H314 Causes severe skin burns and eye damage  
H317 May cause an allergic skin reaction  
H332 Harmful if inhaled  
H351 Suspected of causing cancer  
H336 May cause drowsiness or dizziness

#### Precautionary statements

##### Prevention

P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No Smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/fume/gas/mist/vapor/spray.  
P271 Use only outdoors or in well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear PPE to protect skin/eyes.  
P281 Use personal protective equipment as required.

##### Response

P312 Call a poison center or doctor if you feel unwell.  
P363 Wash contaminated clothing and wash before reuse.

# SAFETY DATA SHEET

**Product Name:** SMART SEAL ROUGH PRIME

**Product Code:** 660 Catalyst

**Date issued:** 5/27/2015

---

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P308 + P313 IF exposed or concerned: Get medical advice/attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Storage/ Disposal

P405 Store locked up.  
P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.  
P403 + P233 Store in well ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.

## Other Hazards

**OSHA Regulatory Status:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

---

## SECTION 3 : COMPOSITION INFORMATION

Chemical Designation	CAS No.	% by Weight
magnesium silicate	14807-96-6	40 - 50%
polyamide resin	68410-23-1	30 - 40%
light aromatic naphtha	64742-95-6	10 - 20%
1,2,4 trimethylbenzene	95-63-6	5 - 10%
triethylenetetramine	112-24-3	1 - 5%
rheological additive	unknown	1 - 5%
cumene	98-82-8	0.1 - 1%

---

## SECTION 4 : FIRST AID MEASURES

General Advice	Show this safety data sheet to the doctor in attendance
Eyes:	Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate medical attention.
Skin:	Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention.
Inhalation:	Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.
Ingestion:	Do not induce vomiting – seek immediate medical attention.
Notes to Physician	Treat symptomatically

---

## SECTION 5 : FIRE FIGHTING MEASURES

Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific Hazards arising from the Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Special protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

---

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Methods for Clean-up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

# SAFETY DATA SHEET

**Product Name: SMART SEAL ROUGH PRIME**

**Product Code: 660 Catalyst**

**Date issued: 5/27/2015**

---

Other Information      None known

---

## **SECTION 7 : HANDLING & STORAGE**

**Handling:** Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

**Storage:** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.

---

## **SECTION 8 :EXPOSURE CONTROLS / PERSONAL PROTECTION**

HMIS is a Health, Flammability and Reactivity rating: **2\*21**

HMIS CODE: **4** – SEVERE HAZARD, **3** – SERIOUS HAZARD, **2** – MODERATE HAZARD, **1** – SLIGHT HAZARD, **0** – MINIMAL HAZARD, \* – Chronic Hazard  
Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

### **Exposure Limits**

<b>Hazardous Components</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>
magnesium silicate	20 mppcf	2 mg/m3 (R)
polyamide resin	NE	NE
light aromatic naphtha	NE	NE
1,2,4 trimethylbenzene	25 ppm	25 ppm
triethylenetetramine	100 ppm	NE
rheological additive	5 mg/m3 (R)	3 mg/m3 (R)
cumene	50 ppm	50 ppm

NE = None established    NA = Not available    (C) = Ceiling limit    (I) = Inhalable fraction    (IFV) = Inhalable fraction and vapor    STEL = Short term exposure limit  
(R) = Respirable fraction

**Engineering Measures**      Ensure adequate ventilation, especially in confined areas.

### **Personal Protective Equipment**

**Eyes/Face:** Safety goggles or full face shield

**Skin:** Protective gloves and impervious clothing.

**Respiratory Protection:** In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Practices:** Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

---

## **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	liquid		
Odor:	Solvent odor	Odor threshold:	Not determined
VOC lb/gal	1.92	VOC (g/L)	230.09
VOC (lb/gal) less exempt	1.92	VOC (g/L) less exempt	230.09
Relative Density (LB/GAL):	11.20	Specific Gravity (g/L):	1.34
Flash Point (F):	110		
Flammability:	Not determined	Upper/lower flammability limits:	Not available
Auto-ignition temperature:	Not determined	Decomposition temperature:	Not determined
Evaporation rate :	Not available		
Vapor Pressure (mmHg) :	Not available	Vapor Density :	Not available
Initial Boiling Point (F):	Not available	Boiling Point Range (F):	Not available
Freezing Point (F):	Not determined	Melting Point (F):	Not determined
pH	Not available	Viscosity	Not available
Solubility (ies):	Not determined		
Partition coefficient: n-octanol/water	Not determined		

---

## **SECTION 10 : STABILITY AND REACTIVITY**

**Chemical Stability:** Stable under normal conditions. Hazardous polymerization does not occur.

# SAFETY DATA SHEET

**Product Name:** SMART SEAL ROUGH PRIME

**Product Code:** 660 Catalyst

**Date issued:** 5/27/2015

---

Conditions to Avoid:	Keep away from open flames, hot surfaces, static electricity and sources of ignition.
Materials to Avoid:	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products:	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility of Hazardous Reactions:	None under normal conditions of use.

---

## **SECTION 11 : TOXICOLOGICAL INFORMATION**

### **Acute Toxicity**

<b>Component</b>	<b>LD50 Oral mg/kg (Rat)</b>	<b>LD50 Dermal mg/kg (Rabbit)</b>	<b>LC50 Inhalation mg/L (Rat, 4 hr.)</b>
magnesium silicate	NA	NA	NA
polyamide resin	NA	NA	NA
light aromatic naphtha	8,400	NA	NA
1,2,4 trimethylbenzene	5,000	18,000	NA
triethylenetetramine	2,500	805	NA
rheological additive	NE	NE	NE
cumene	NA	NA	NA

### **Chronic Toxicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:

<b>Component</b>	<b>IARC</b>	<b>NTP</b>	<b>OSHA</b>
cumene	2B – Possible Human Carcinogen	Not listed	Listed

---

## **SECTION 12 : ECOLOGICAL INFORMATION**

No ecological information available

## **SECTION 13 : DISPOSAL CONSIDERATION**

Waste Disposal Method                      Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## **SECTION 14 : TRANSPORT INFORMATION**

Contact the manufacturer for shipping information.

## **SECTION 15 : REGULATORY INFORMATION**

US TSCA:                                      Yes – All components are listed or exempt

### **Federal Regulations**

#### **SARA 311/312 hazardous categorization**

Acute Health Hazard	YES
Chronic Health Hazard	YES
Fire Hazard	NO
Sudden Release of Pressure Hazard	NO
Reactive Hazard	NO

#### **SARA 313**

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

<b>Chemical Designation</b>	<b>Cas No.</b>	<b>Weight %</b>
-----------------------------	----------------	-----------------

# SAFETY DATA SHEET

**Product Name: SMART SEAL ROUGH PRIME**

**Product Code: 660 Catalyst**

**Date issued: 5/27/2015**

---

1,2,4 trimethylbenzene

95-63-6

5 - 10%

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)**

Chemical Designation	Cas No.	Weight %
cumene	98-82-8	0.1 - 1%

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

**State Regulations**

**California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

**SECTION 16 : OTHER INFORMATION**

Date issued: 5/27/2015      VER 01

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.